



INSTRUCTIONS

-J00785

REV. 10-1-82

Kit Number 51189-83

PASSENGER GRAB STRAP - XLX MODELS

General

This passenger grab strap is designed for use on XLX models. This kit contains the following parts:

| ITEM | DESCRIPTION | QTY |
|------|-------------|-----|
| 1 | Grab strap | 1 |
| 2 | Washer | 4 |
| 3 | Screw | 2 |
| 4 | Nut | 2 |

⚠ WARNING

For passenger protection, this grab strap is to be installed with footpegs and pillion seat for the passenger. These parts are available separately from your Harley-Davidson dealer.

Installation

1. See Figure 1. Use a piece of coated wire or string tied to the strap end. Lubricate the strap end with soap and with the strap seams down, pull strap between fender support and fender.

⚠ CAUTION

Pull strap between fender and fender support. Do not push strap through using a screwdriver or sharp instrument. Damage to surrounding parts may occur.

2. After strap has been pulled through, bend end of strap up and align holes in strap with holes in fender support and fender.

NOTE

Use a center punch or awl to align holes in strap, fender support and fender.



Figure 1. Strap Installation

3. Install flat washer on screw and insert screw through strap, fender support and fender.
4. Install flat washer and secure with nut.
5. Repeat Steps 1 through 4 to install strap on opposite side.