

# INSTRUCTIONS

-J00938 REV. 5-20-02

Kit Numbers 32054-98, 32055-98, 32056-98, and 32072-98

## SCREAMIN' EAGLE SPARK PLUG WIRE KIT

#### General

These spark plug wires are designed for installation on 1998 and later XL1200S models.

32054-98	Black
32055-98	
32056-98	
32072-98	Yellow

### Installation

## **A**WARNING

To avoid accidental start-up of motorcycle, and possible personal injury, disconnect the battery cables (negative cable first) before performing any of the following procedures. If the positive cable should contact ground with the negative cable installed, the resulting sparks may cause a battery explosion resulting in death or serious injury.

## **AWARNING**

Gasoline is extremely flammable and highly explosive under certain conditions. Do not smoke or allow open flame or sparks anywhere in the area when draining or servicing the fuel system. Drain gasoline into approved gasoline container only. Failure to follow instructions could result in death or serious injury.

#### NOTE

A Service Manual for your motorcycle is available from your Harley-Davidson dealer.

 Remove fuel tank following instructions in appropriate Service Manual. Place tank in a safe location where it will not be damaged or scratched. Set all fuel tank hardware aside for later reinstallation.


#### IMPORTANT NOTE

When installing spark plug wires, remove only **one wire at a time** and install the wire to replace it before moving on to the next wire.

- Follow Spark Plug Wire Length Chart and Wire Routing Illustration shown below to install spark plug wires. Make sure boots are seated firmly on plugs and into the coil towers. Place wires back into original clips as shown.
- Re-assemble fuel tank to frame following Service Manual procedures.

# Spark Plug Wire Length Chart

Plug Wire #	Approx. Length	Plug Boot Style
1	16 1/2"	Short
2	15 1/2"	Long
3	20"	Short
4	15 3/4"	Long



Spark Plug Wire Routing